



DB400 / DB425 DOLPHIN PANEL MOUNTED ELECTRONIC INFRARED TAP

 > Touch Free Tap – for ultimate hygiene – prevents cross contamination > Quality polished or brushed chrome plated brass finishes available from stock – other finishes availab to special order > Water Supply: Single inlet cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications 	le DIAMETER PROJECTION	38мм 170мм
 Flow rate – 3.5 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 	PRODUCT CODES	
 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire) > Flow time once user's hands are removed from the tap - 1 second (adjustable by using remove cont DB51) > Interchangeable STD M22/24 Neoperl Aerator insert > Tap settings may be adjusted by using remote control (DB51) > Power Source: 6 x AA Battery / plug in 9v Transformer. Power Connections: tap female, power sour male > Operating pressure 0.5 - 8.0 bar (7 - 116 PSI) > Maximum water temperature 70°C > To combat Legionella, hygiene flush feature runs the tap for 25 seconds, 24 hours after the last use of the tap. This flush time or 24 hours interval cannot be changed and is not based on real time, the feature can only be switched on or off using a compatible remote control(DB51). Taps are supplied with this feature switched on > 2 year manufacturer's warranty > WRAS approved, and complies with SKA rating criteria > To special order we can supply a threaded tail extension kit > Fully BREEAM compliant and contributes to up to five BREEAM WAT 1 credits. > Listed on the Government's Water Technology List (WTL) as part of the Enhanced Capital Allowan 	DB400C - Battery powered, roDB400S-2 - Battery powere DB425C - Transformer pow finish DB425S-2 - Transformer po rce	d, satin finish rered, polished
		424 202224 JK