PRODUCT-NO.: 230628

## DHC-E 12 COMPACT INSTANTANEOUS WATER HEATER

The electronic compact instantaneous water heater DHC-E reliably supplies one or more draw-off points. Up to the output limit, hot water always flows at precisely the required temperature. The electronic control ensures that the appliance output adjusts automatically subject to the temperature of the water supply and the selected DHW temperature. The DHW temperature is variably adjustable. The tubular heater system with pressure-tested copper casing is suitable for soft water areas.



## The main features

STIEBEL ELTRON

For one or several draw-off points

Constant temperature up to the output limit

Simple and secure operation

Easy and quick installation

Works even with low water pressure

ETL compliant

Splashproof to IP 24







Туре	DHC-E 8/10	DHC-E 12
Part no.	224201	230628
Rated output	9,6 kW	12 kW
Height	360 mm	360 mm
Width	200 mm	200 mm
Depth	110 mm	110 mm

## Technical data

Rated voltage 1	208 V	208 V
Rated output 1	5,4/7,2 kW	9 kW
Rated current 1	28/35 A	44 A
Fuse 1	30/50 A	60 A
Rated voltage 2	220 V	220 V
Rated output 2	6,0/8,1 kW	10 kW
Rated current 2	30/50 A	46 A
Fuse 2	40/50 A	60 A
Rated voltage 3	230 V	230 V
Rated output 3	6,6/8,8 kW	11 kW
Rated current 3	31/39 A	48 A
Fuse 3	40/50 A	60 A
Phases	1/N/PE ~220-240V	1/N/PE ~220-240V
Frequency	50/60 Hz	50/60 Hz
Temperature adjustment	30-60 °C	30-60 °C
Energy efficiency class	А	А



STIEBEL ELTRON

Technik zum Wohlfühlen

IP-Rating	IP24	IP24
Colour	white	white
Weight	2,7 kg	2,7 kg



## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help: Call 0151 346 2300 Or send an e-mail to sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.