

SHZ 150 S (GB)

WALL MOUNTED CYLINDERS 30 TO 150 L

PRODUCT-NO.: 232788

The main features

Universal flanged immersion heater for dual circuit operation, optional single circuit operation/manual rapid heat-up operation

Infinitely variable temperature selection from 35 °C to 70 °C

Suitable safety valve included in standard delivery

Electronic heat content indication via LED in the user interface

Signal anode with indicator lamp in the user interface; can be replaced without removing the flange (50 - 150 l)

High-grade thermal insulation with the lowest heat losses

Maintenance free impressed current anode

Radiator connections through complete flanged plug

Drain valve with G 3/4 hose connection

Can also be installed with plastic pipework systems





Type	SHZ 30 S (GB)	SHZ 50 S (GB)	SHZ 100 S (GB)
Part no.	232783	232784	232786
Rated capacity	30 l	50 l	100 l
Width	410 mm	510 mm	510 mm
Height	846 mm	816 mm	1126 mm
Depth	420 mm	510 mm	510 mm

Technical data

Connected load with ~ 230 V	1-4 kW	1-4 kW	1-4 kW
Power supply	1/N/PE	1/N/PE	1/N/PE
Rated voltage	230 V	230 V	230 V
Frequency	50 Hz	50 Hz	50 Hz
Standby power consumption/24 h	0,46 kWh	0,54 kWh	0,86 kWh
Colour	white	white	white
IP-Rating	IP24	IP24	IP24
Energy efficiency class	B	C	C
Weight	22,90 kg	27,60 kg	39,50 kg



Type	SHZ 150 S (GB)
Part no.	232788
Rated capacity	150 l
Width	510 mm
Height	1521 mm
Depth	510 mm

Technical data

Connected load with ~ 230 V	1-4 kW
Power supply	1/N/PE
Rated voltage	230 V
Frequency	50 Hz
Standby power consumption/24 h	1,10 kWh
Colour	white
IP-Rating	IP24
Energy efficiency class	C
Weight	52,00 kg