



# HRT4-ZW and HRT4-B Electronic Room Thermostats

Wireless or wired, this new range of purpose designed room thermostats from Horstmann offer the latest energy saving control technology combined with established Horstmann design and manufacturing expertise, making them suitable for use in most types of heating system.

They are also perfect partners for use with Horstmann Programmers and Zone valves.

- Wireless or wired (battery operated) versions
- TPI temperature control software
- Clear backlit digital display
- Temperature range 5-30°C
- Easy to install and use

Horstmann.
Together,
we're in control.



## Horstmann. Together, we're in control.

### **SPECIFICATION**

### Thermostat specification HRT4-ZW

**POWER SUPPLY** 

alkaline batteries

TEMPERATURE ACCURACY +/- 0.5°C TRANSMITTER FREQUENCY 868MHz

DIMENSIONS POLLUTION CONTROL DESIGN STANDARD TEMPERATURE RANGE

Degree 2 EN60730 - 2-9 5°C - 30°C

86 x 86 x 36.25mm

RATED IMPULSE VOLTAGE ENCLOSURE PROTECTION

Cat 2 - 2500V

OPERATING TEMPERATURE 0-40°C

IP30

RANGE DOUBLE INSULATED

Thermoplastic,

CASE MATERIAL

flame retardant

POWER SUPPLY CONTACT TYPE

230V AC 50Hz Micro disconnection

Voltage free

CONTACT RATING

3(1) Amps 230V AC

OPERATING TEMPERATURE 0-40°C

RANGE

DOUBLE INSULATED

RATED IMPULSE VOLTAGE **POLLUTION CONTROL ENCLOSURE PROTECTION** 

Cat 2 - 2500V Degree2 **IP30** 

CASE MATERIAL

Thermoplastic, flame retardant

DIMENSIONS

86 x 86 x 36.25mm

**POWER SUPPLY** 

2 x AAA

CONTACT RATING TEMPERATURE ACCURACY

alkaline batteries 3 (1)amp 230V AC +/- 0.5°C (at 21°C

**CONTACT TYPE** 

with 0.5 amp load) Micro disconnection

**VOLT FREE CHANGEOVER** 

86 x 86 x 36.25mm

**DIMENSIONS** POLLUTION CONTROL DESIGN STANDARD TEMPERATURE RANGE

RATED IMPULSE VOLTAGE **ENCLOSURE PROTECTION** 

Degree 2 EN60730 - 2-9 5°C - 30°C Cat 2 – 25<u>00V</u> IP30







### HRT4-ZW with ASR-ZW receiver

Wireless Z-Wave electronic room thermostat and ASR-ZW receiver with TPI energy saving software - avoids disruptive and time consuming wiring compatible with most heating systems.

With proven Z-Wave wireless technology using the 868.42 MHz operating frequency, the thermostat unit features a constant RF status display with its receiver being mains powered with volt free contacts.

### HRT4-B

The HRT4-B is a battery operated room thermostat with TPI energy saving software - ideal for use with a new installation or as a replacement for an existing room thermostat.

The HRT4-B has 3 amp volt free change over contacts - making it ideal for use with combi boilers as well as conventional mains operated equipment.

Designed to look good, these thermostats will out perform many older styles of thermostat and can often produce savings in the order of 10% over and above those achieved by traditional units using older technology.

The TPI settings are adjustable for Gas, Oil and Electric systems and the display shows 1°C resolution, heating ON symbol, target and actual temperatures at the touch of the dial and an energy saving back light that switches off after 7 seconds.

Available in wireless and wired versions - for new and replacement situations - there is a Horstmann thermostat to suit most installations.

The wireless version employs the latest Z-Wave radio frequency (RF) technology resulting in a highly reliable and trouble free wireless connection with minimal setting up procedures.

Thermostat battery life is in excess of two years using 2 standard AAA batteries which are supplied. A battery low indication tells the user when the batteries need changing.

