



Concrete curing cable

Series-resistive 2-conductor with screen


Usage

To start curing concrete in cold temperatures
To accelerate the drying of the concrete
Heating during the construction process

 Cable  40 W/m  Plug

- ✓ Easy to install
- ✓ Ensures and speeds up the construction process

BHS is a heating cable specially designed for curing and drying concrete, as well as heating. The system speeds up concrete curing and enables formwork to be dismantled sooner. The heating cable, which is fixed to the reinforcement, can be reconnected at a later stage for effective drying or heating. The heating cable is equipped with a connection cable. The heating cable is of the 2-conductor type, which makes it simple and quick to lay.



Specifications

Connection voltage	230 V
Length Connection cable	2,0 m
Number of conductors	2 pcs
Bending radius, min.	50 mm
Diameter	4 mm
Output	40 W/m
Installation temperature, min.	-10 °C
Insulation material intermediate	XLPE
Insulation material inner	XLPE
Insulation material outer	XLPE
Cable type	Series-resistive 2-conductor with screen
Enclosure class	IP44, IP67
Mechanical classification	M2
Protective conductor	Aluminium foil
UV resistance	No

Documents

 CE document

 Manual

Warranty

The general terms of delivery are listed below.
Our warranty terms

Article list

Article number	Length (m)	Output (W)	Output (W/m)	Connection cable (mm ²)
8960491	55	2200	40	1,0
8960493	35	1400	40	1,0
8960494	20	735	40	1,0
8960495	10	380	40	1,0
8960496	85	3500	40	1,5
8960497	3.3	130	40	1,0

Supplementary products



Distribution
centre



BHS Series
connection
adapter

Learn more about this product: <https://www.ebeco.com/products/temporary-heating-solutions/concrete-curing-cable>