

DHM 4 Set

MINI INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 236451

The DHM mini instantaneous water heater supplies a single draw-off point where hot water is required infrequently and in small volumes. It heats the water very quickly at a DHW output of up to two and a half litres per minute. Its small dimensions enable flexible installation even in the tightest of spaces. The DHM is suitable for undersink installation. It is installed with commercially available pressure taps.



The main features

Hydraulically controlled mini instantaneous water heater for energy efficient and water saving supply of a single hand wash basin

Undersink installation

Can be operated with pressurised and non-pressurised taps

Special aerator for perfect flow pattern

Instant hot water thanks to rapid and maintenance-free bare wire heating system

Quick PROFI-RAPID installation

International: Also suitable for showers with inlet temperatures above 20 °C



Type	DHM 3 Set	DHM 4 Set	DHM 6 Set
Part no.	236450	236451	236452
Rated output	3,53 kW	4,4 kW	5,7 kW
Width	190 mm	190 mm	190 mm
Height	143 mm	143 mm	143 mm
Depth	82 mm	82 mm	82 mm

Technical data

Rated voltage 1	200 V	200 V	200 V
Rated output 1	2,7 kW	3,3 kW	4,3 kW
Rated current 1	13,3 A	16,7 A	21,6 A
Fuse 1	16 A	20 A	25 A
Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz
Rated voltage 2	220 V	220 V	220 V
Rated output 2	3,2 kW	4,0 kW	5,2 kW
Rated current 2	14,5 A	18,2 A	23,6 A
Fuse 2	16 A	20 A	25 A
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Rated voltage 3	230 V	230 V	230 V
Rated output 3	3,53 kW	4,4 kW	5,7 kW
Rated current 3	15,2 A	19,1 A	24,7 A
Fuse 3	16 A	20 A	25 A
Frequency 3	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Water connection	G 3/8 A	G 3/8 A	G 3/8 A
Specific conductivity $\sigma_{15 \leq}$ (at $\vartheta_{\text{cold}} \leq 25 \text{ °C}$)	909 $\mu\text{S/cm}$	909 $\mu\text{S/cm}$	909 $\mu\text{S/cm}$

Specific resistance $\rho_{15} \geq$ (at $\vartheta_{cold} \leq 25\text{ °C}$)	1100 Ω cm	1100 Ω cm	1100 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{cold} > 25\text{ °C}$)	909 $\mu S/cm$	909 $\mu S/cm$	909 $\mu S/cm$
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{cold} > 25\text{ °C}$)	1100 Ω cm	1100 Ω cm	1100 Ω cm
Energy efficiency class	A	A	A
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight	1,60 kg	1,60 kg	1,60 kg